




□ 回路図 : CIRCUIT

□ 外形寸法図 : OUTLINE DRAWING



PRHMB150E6



PRHMB150E6C

Dimension: [mm]

□ 最大定格 : MAXIMUM RATINGS (T_c = 25°C)

Item	Symbol	Rated Value			Unit
コレクタ・エミッタ間電圧 Collector-Emmitter Voltage	V _{CEs}	600			V
ゲート・エミッタ間電圧 Gate-Emmitter Voltage	V _{GES}	±20			V
コレクタ電流 Collector Current	DC	150			A
	1ms	300			
コレクタ損失 Collector Power Dissipation	P _C	560			W
接合温度 Junction Temperature Range	T _j	-40~+150			°C
保存温度 Storage Temperature Range	T _{stg}	-40~+125			°C
絶縁耐圧(Terminal to Base AC, 1 minute) Isolation Voltage	V _{ISO}	2,500			V (RMS)
締め付けトルク Mounting Torque	F _{tor}	PDMB150E6	3 (30.6)	PDMB150E6C	3 (30.6)
			3 (30.6)		2 (20.4)

□ 電気的特性 : ELECTRICAL CHARACTERISTICS (T_c = 25°C)

Characteristic	Symbol	Test Condition	Min.	Typ.	Max.	Unit
コレクタ遮断電流 Collector-Emmitter Cut-Off Current	I _{CEs}	V _{CE} = 600V, V _{GE} = 0V	—	—	1.0	mA
ゲート漏れ電流 Gate-Emmitter Leakage Current	I _{GES}	V _{GE} = ±20V, V _{CE} = 0V	—	—	1.0	μA
コレクタ・エミッタ間飽和電圧 Collector-Emmitter Saturation Voltage	V _{CE(sat)}	I _C = 150A, V _{GE} = 15V	—	2.1	2.6	V
ゲートしきい値電圧 Gate-Emmitter Threshold Voltage	V _{GE(th)}	V _{CE} = 5V, I _C = 150mA	4.0	—	8.0	V
入力容量 Input Capacitance	C _{ies}	V _{CE} = 10V, V _{GE} = 0V, f = 1MHz	—	7,500	—	pF
スイッチング時間 Switching Time	上昇時間 Rise Time	V _{CC} = 300V R _l = 2.0Ω R _g = 5.1Ω V _{GE} = ±15V	—	0.15	0.30	μs
	ターンオン時間 Turn-on Time		—	0.25	0.40	
	下降時間 Fall Time		—	0.10	0.35	
	ターンオフ時間 Turn-off Time		—	0.35	0.70	

□ フリーホイールダイオードの特性 : FREE WHEELING DIODE RATINGS & CHARACTERISTICS (T_c = 25°C)

Item	Symbol	Rated Value		Unit
順電流 Forward Current	DC	150		A
	1ms	300		

Characteristic	Symbol	Test Condition	Min.	Typ.	Max.	Unit
順電圧 Peak Forward Voltage	V _F	I _F = 150A, V _{GE} = 0V	—	1.9	2.4	V
逆回復時間 Reverse Recovery Time	t _{rr}	I _F = 150A, V _{GE} = -10V di/dt = 300A/μs	—	0.15	0.25	μs

□ 熱的特性 : THERMAL CHARACTERISTICS

Characteristic	Symbol	Test Condition	Min.	Typ.	Max.	Unit
熱抵抗 Thermal Impedance	R _{th(j-c)}	IGBT	—	—	0.22	°C/W
		Diode	—	—	0.45	









Fig.7- Collector Current vs. Switching Time (Typical)




Fig.8- Series Gate Impedance vs. Switching Time (Typical)




Fig.9- Collector Current vs. Switching Time




Fig.10- Series Gate Impedance vs. Switching Time




Fig.11- Collector Current vs. Switching Loss




Fig.12- Series Gate Impedance vs. Switching Loss




Fig.13- Forward Characteristics of Free Wheeling Diode (Typical)




Fig.14- Reverse Recovery Characteristics (Typical)




Fig.15- Reverse Bias Safe Operating Area




Fig.16- Transient Thermal Impedance

